

## MODEL INFORMATION TYPE DIMENSIONS WEIGHT CFM SPECS SUPPLY PLENUM<sup>1</sup> **EXHAUST PLENUM LENGTH** WIDTH HEIGHT 352 lbs 2659 @ 0.12 ESP 132" 51" 24" 3324 @ 0.5 ESP

Installing contractor have the responsability to ensure hood cleareance from limited-combustible and combustible materials is compliant with local code requirements.

<sup>1</sup> Sold Separately


STANDARD COMPONENTS INCLUDED								
MOUNTING BRACKET 12-GAUGE GALVANIZED	Incandescent Light Fixture	Standoff	Grease Drain	Grease Cup Stainless Steel NSF	Grease Filter Stainless Steel UL 1046			
QTY	UL Listed (Included Component)	3" back standoff included	QTY	QTY	QTY	Length	Height	
6			2	2	0	16"	16"	
	QTY				4	20"	16"	
	2				2	25"	16"	


## **VSE48 ETL-11**

## STAINLESS STEEL EXHAUST HOOD N.S.F. LISTED. CONFORMS TO NFPA96

Hood Constructed with continuous liquid-tight weld in conformance to IMC 2012 507.7.1.

Hood material: 18 Gauge 430 STAINLESS STEEL (#3 polish) where exposed.





	SUGGESTED COMPONENTS							
Exhaust Collar		Side	Shipping Crate					
		Standoff	Dimensions (in) and Weight (lb)					
16-Gauge Cold Rolled Build			Length:	136"				
		□ NONE □ 3"	Width:	55"				
QTY	Size		Height:	32"				
1	14" x 22"		Weight:	462 lbs				

Superior Hoods		VSE48 ETL-11						
PO BOX 47607 - ATLANTA, GA 30360 PHONE: 770.936.0770 - www.superiorhoods.com			VSE48 ETL HOOD MODEL STANDARD SPEC SHEET					
APPROVED			SIZE	CODE		DWG NO		REV
CHECKED			В					01
DRAWN	PRODUCTION	2023	SC	ALE: 1:33	WEIC	SHT: 352 lbs	SHEET: 1/	1